Safety Data Sheet: NC-123 PLUS AEROSOL

Supercedes Date 07/21/2010

Issuing Date 08/01/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name NC-123 PLUS AEROSOL Recommended use Lubricant Clear coating Information on Manufacturer CHEMSEARCH DIV. OF NCH CORP.

BOX 152170 IRVING, TX 75015 Product Code 5625
Chemical nature Petroleum distillates
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Amber Physical State Liquid Odor Solvent

GHS

Classification

Physical Hazards

Flammable aerosols Category 2
Gases under pressure Compressed Gas

Health Hazard

Aspiration Toxicity

Acute Dermal Toxicity

Acute Inhalation Toxicity - Gas

Acute Inhalation Toxicity - Dusts and Mists

Category 4

Skin Corrosion/Irritation

Category 2

Skin Corrostor/irritation Category 2
Serious Eye Damage/Eye Irritation Category 2B
Specific target organ systemic toxicity (single exposure) Category 3
Specific target organ systemic toxicity (repeated exposure) Category 2

Other hazards

None

Labeling Signal Word DANGER



Hazard Statements

H223 - Flammable aerosol

H331 - Toxic if inhaled

H336 - May cause drowsiness or dizziness

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H320 - Causes eye irritation

H304 - May be fatal if swallowed and enters airways

H373 - May cause damage to organs through prolonged or repeated exposure

H280 - Contains gas under pressure; may explode if heated

Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P280 - Wear protective gloves, protective clothing and eye protection.

P260 - Do not breathe vapor, mist or gas

P271 - Use in a well-ventilated area.

P270 - Do not eat, drink or smoke when using this product

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position

comfortable for breathing.

P312 - Call a physician if unwell.

P302+ P352 - IF ON SKIN: Wash with plenty of soap and water

P332 + P313 - If skin irritation occurs, get medical attention.

P362 - Take off contaminated clothing and wash before reuse

 $\mbox{P305} + \mbox{P351} + \mbox{P338}$ - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists, get medical attention.

P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a physician if unwell.

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 $^{\circ}\text{F}$

P403 - Store in a well-ventilated place

P501 - Dispose of contents and container in accordance with applicable regulations.

25 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Petroleum distillates, hydrotreated light	64742-47-8	10-30
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	10-30
Petroleum distillate	8052-41-3	10-30
Propane	74-98-6	7-13
Mineral oil	8012-95-1	1-5
Butane	106-97-8	1-5
Nonane	111-84-2	1-5
Barium sulfonate	61790-48-5	1-5
Paraffin wax	8002-74-2	1-5

4. FIRST AID MEASURES

General advice Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, or gas.

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation

develops and persists.

Skin Contact Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never

give anything by mouth to an unconscious person.

Notes to physician Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and

enters airways.

5. FIRE-FIGHTING MEASURES

Flash Point106 °F / 41 °CMethodSeta closed cupFlammability Limits in Air % .Upper 9.5Lower 0.8

Suitable Extinguishing Media

Water spray. Foam. Dry chemical. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Extremely flammable. Solvent vapors are heavier than air and may spread along floors. Flame extension: 24 inches / 61 cm and Burnback: 4 inch / 10 cm.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) - 3

NFPA Health 2 Flammability 4 Instability 0 Health 2 Flammability 4 Instability 0 Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled

containers.

Neutralizing Agent Not applicable.

7. HANDLING AND STORAGE

Handling Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures

against static discharges. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or

gas.

Storage Keep away from heat and sources of ignition. Store in original container. Keep containers tightly

closed in a dry, cool and well-ventilated place.

Storage TemperatureMinimum35 °F / 2 °CMaximum120 °F / 49 °CStorage ConditionsIndoorXOutdoorHeatedRefrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated light	5 mg/m ³ as oil mist	10 mg/m ³ as oil mist	No data available
Solvent naphtha (petroleum), medium aliphatic	No data available	No data available	No data available
Petroleum distillate	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³	IDLH: 20000 mg/m ³
			Ceiling: 1800 mg/m ³
			TWA: 350 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm
		11	TWA: 1000 ppm TWA: 1800 mg/m ³
Mineral oil	TWA: 5 mg/m ³	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³
			STEL 10 mg/m ³
			TWA: 5 mg/m ³
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Nonane	TWA: 200 ppm	No data available	TWA: 200 ppm TWA: 1050 mg/m ³
Barium sulfonate	No data available	No data available	No data available
Paraffin wax	TWA: 2 mg/m ³	No data available	TWA: 2 mg/m ³

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Wear suitable protective clothing, Impervious gloves.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators.

be achieved by the use of local exhaust ventilation and good general extraction.

General Hygiene Considerations Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Viscosity **Physical State** Liquid Non viscous Color Amber Odor Solvent **Odor Threshold** Not applicable Transparent **Appearance** рΗ Not applicable Specific Gravity 0.733 **Evaporation Rate** 21.9 (Butyl acetate=1) Percent Volatile (Volume) 94.4 VOC Content (%) 93.8 VOC Content (g/L) 687 **Vapor Pressure** 1257 mmHg @ 70°F Vapor Density 1.9 (Air = 1.0)

Solubility Negligible n-Octanol/Water Partition No data available **Decomposition Temperature** Melting Point/Range No data available No data available **Boiling Point/Range** No data available Flammability (solid, gas) No data available Flash Point 106 °F / 41 °C Method Seta closed cup

Autoignition Temperature No information available.

Flammability Limits in Air % Upper 9.5 Lower 0.8

10. STABILITY AND REACTIVITY

Chemical Stability Stable, Hazardous polymerization does not occur.

Conditions to Avoid Keep away from open flames, hot surfaces, and sources of ignition

Incompatible Products Strong oxidizing agents **Hazardous Decomposition Products** Carbon oxides, Sulfur oxides. **Possibility of Hazardous Reactions** None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):

Oral LD50 No information available **Dermal LD50** No information available

Inhalation LC50

No information available Gas Mist No information available Vapor No information available

Principle Route of Exposure Eye contact, Skin contact, Inhalation. **Primary Routes of Entry** Inhalation

Acute Effects

Eyes Causes eye irritation. Skin Causes skin irritation.

Causes respiratory tract irritation. Inhalation may cause central nervous system effects. May cause Inhalation

central nervous system depression. Symptoms and signs include headache, dizziness, fatigue,

muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and

incoordination. May be fatal if swallowed and enters airways.

Chronic Toxicity Prolonged or repeated inhalation may cause damage to the lungs. Prolonged skin contact may defat

the skin and produce dermatitis. Liver and kidney injuries may occur.

Target Organ Effects Central nervous system, Respiratory system, Kidney, Liver, Heart.

Aggravated Medical Conditions Neurological disorders, Kidney disorders, Liver disorders, Skin disorders, Heart disease.

Component Information

Ingestion

Acute	To	cicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Petroleum distillates,	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h	no data available	no data available
hydrotreated light					
Solvent naphtha (petroleum),	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h	no data available	no data available
medium aliphatic					
Petroleum distillate	no data available	no data available	no data available	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Mineral oil	no data available	no data available	= 2062 ppm (Rat) 4 h	no data available	no data available
Butane	no data available	no data available	= 658 g/m ³ (Rat) 4 h	no data available	no data available
Nonane	no data available	no data available	= 3200 ppm (Rat) 4 h	no data available	no data available
Barium sulfonate	no data available	no data available	no data available	no data available	no data available
Paraffin wax	> 3750 mg/kg (Rat)	> 3600 mg/kg (Rabbit)	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Petroleum distillates, hydrotreated light	no data available	no data available	no data available		respiratory system, liver, kidney, CNS
Solvent naphtha (petroleum), medium aliphatic	no data available	no data available	no data available	no data available	CNS, liver, kidneys
Petroleum distillate	no data available	no data available	no data available	no data available	eyes,CNS,respiratory system,skin,kidneys
Propane	no data available	no data available	no data available	no data available	CNS, heart
Mineral oil	no data available	no data available	no data available	no data available	eyes, respiratory system, skin
Butane	no data available	no data available	no data available	no data available	CNS, heart
Nonane	no data available	no data available	no data available	no data available	eyes,CNS,respiratory system,skin
Barium sulfonate	no data available	no data available	no data available	no data available	no data available
Paraffin wax	no data available	no data available	no data available	no data available	eyes, respiratory system, skin

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Carcinogenicity	THE LADI	e below illulcates wrieti	iei each agency has listed t	arry irrigiteurerit as a	carcinogen.
Component	ACGIH	IARC	NTP	OSHA	Other
Petroleum distillates, hydrotreated light	not applicable	not applicable	not applicable	not applicable	not applicable
Solvent naphtha (petroleum), medium aliphatic	not applicable	not applicable	not applicable	not applicable	not applicable
Petroleum distillate	not applicable	not applicable	not applicable	not applicable	not applicable
Propane	not applicable	not applicable	not applicable	not applicable	not applicable
Mineral oil	not applicable	not applicable	not applicable	not applicable	not applicable
Butane	not applicable	not applicable	not applicable	not applicable	not applicable
Nonane	not applicable	not applicable	not applicable	not applicable	not applicable
Barium sulfonate	not applicable	not applicable	not applicable	not applicable	not applicable
Paraffin wax	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information Component Information No information available.

component information					
Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Petroleum distillates, hydrotreated	no data available	LC50 = 45 mg/L Pimephales	no data available	LC50= 4720 mg/L 96 h	N/A
light		promelas 96 h			
·		LC50 = 2.2 mg/L Lepomis			1 1

		macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h			
Solvent naphtha (petroleum), medium aliphatic	EC50 = 450 mg/L Pseudokirchneriella subcapitata 96 h	LC50 = 800 mg/L Pimephales promelas 96 h	no data available	EC50> 100 mg/L 48 h	N/A
Petroleum distillate	no data available	no data available	no data available	no data available	N/A
Propane	no data available	no data available	no data available	no data available	2.3
Mineral oil	no data available	no data available	no data available	no data available	N/A
Butane	no data available	no data available	no data available	no data available	2.89
Nonane	no data available	no data available	no data available	no data available	N/A
Barium sulfonate	no data available	no data available	no data available	no data available	N/A
Paraffin wax	no data available	no data available	no data available	no data available	N/A

Persistence and Degradability

No information available. Bioaccumulation No information available. Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Dispose of in accordance with local regulations.

Container Disposal Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be

taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Consumer commodity

Hazard Class

Description Consumer commodity ,ORM-D,

TDG

Hazard Class 2.1 UN-No UN1950

ICAO

UN-No UN1950 **Proper Shipping Name** Aerosols **Hazard Class** 2.1

Aerosols, UN1950 LTD. QTY. **Shipping Description**

IATA

UN1950 UN-No

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1 **ERG Code** 10L

UN1950, Aerosols, flammable, 2.1 LTD. QTY. **Shipping Description**

IMDG/IMO

Aerosols **Proper Shipping Name Hazard Class** 2.1 UN-No UN1950 EmS No. F-D, S-U

Shipping Description UN1950, Aerosols, 2.1 LIMITED QUANTITIES

15. REGULATORY INFORMATION

Inventories

TSCA Complies DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Barium sulfonate	61790-48-5	1-5	1.0

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard	
Yes	Yes	Yes	Yes	No	
CERCLA					
Comp	onent	Hazardous Substance	es RQs	CERCLA EHS RQs	
Petroleum distillate	s, hydrotreated light	Not applicable		Not applicable	
Solvent naphtha (petroleum), medium aliphatic		Not applicable		Not applicable	
Petroleum distillate		Not applicable		Not applicable	
Propane		Not applicable		Not applicable	
Mineral oil		Not applicable		Not applicable	
Butane		Not applicable		Not applicable	
Nonane		Not applicable		Not applicable	
Barium sulfonate		Not applicable		Not applicable	
Paraffin wax		Not applicable		Not applicable	

16. OTHER INFORMATION

Prepared By Angela Hutson Supercedes Date 07/21/2010 Issuing Date 08/01/2013

Reason for RevisionNo information available.GlossaryNo information available.List of References.No information available.

CHEMSEARCH DIV. OF NCH CORP.assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.